

DF375
King Construction



Available In 6x4 & 8x4 Configuration



Ghandhara Nissan Limited

Head Office:


F-3, Hub Chowki Road,
S.I.T.E, Karachi. UAN # 021-111-190-190,
Tel: 021-32556901-10,
Fax: 021-32556911-12


Rawalpindi Office:

Gammon House Plot
no. 400/2 Peshawar Road, Rawalpindi.
Ph: 051-5465742, 5166939
Fax: 051-5465503

Lahore Office:

Chowk Al-Saeed, Nain Sukh,
Sagiyah By Pass, Lahore.
Ph: 042-37163931
Fax: 042-37163932

 DongFeng Pakistan

www.ghandharanissan.com.pk 


DONGFENG
Trucks

■ DONGFENG DF375 DUMP TRUCK 6x4 & 8x4 Truck Chassis

Type / Model	6x4 K24Y	8x4 K36Y
--------------	----------	----------

Vehicle Weights

G.V.W.	30,000 kg	45,000 kg
Curb Weight (chassis)	10,500 kg	11,600 kg

Chassis Dimensions (mm)

Overall Chassis Length	7,800	9,900
Cab Width	2,500	2,500
Cab Height (Unladen)	3,210	3,130
Wheel Base	4,050 + 1,350	1850+4200+1350
Front/Rear Overhang	1,500 / 900	1,500 / 1,000
Maximum Gradeability	30%	30%
Maximum Speed	75 (Km/h)	75 (Km/h)
Ground Clearance	300	285

Engine

Make & Model	CUMMINS LK375 33
Emission Level	Euro II
Maximum Power	375HP at 2000rpm
Maximum Torque	1600Nm at 1400rpm
Number of Cylinders	6
Displacement (CC)	9,500
Cylinder bore (mm)	116.5
Stroke (mm)	148
System	Water Cooled, Turbocharge, After Cooled.

Gear Box / Transmission

Type	12JSD180T
Number of Gears	12 Forward Gears & 2 Reverse, Synchronization

Fuel Tank

Type	Steel fuel tank with lockable cap	
Capacity	280Liters	350 Liters

Type / Model	6x4 K24Y	8x4 K36Y
--------------	----------	----------

Frame Dimensions (mm)

Frame Width (Front)	940	940
Frame Width (Rear)	860	860
Frame Section Height	300	300
Frame Section (Width)	90	90

Clutch

Make	VALEO
Type	430mm (17 Inches)
Operating System	Hydraulic control with air booster pulling.

Brake System

Service Brakes: Full air brake system, split pneumatic circuit, ABS.
Parking Brakes: Spring brakes acting on rear axles, exhaust brake.

Axles

Make:	DANA
Front:	Elliot type, "I" Beam Section
Rear:	Hub Reduction, Tandem axle with axle lock & Wheel Lock
Final Ratio:	5.26

Suspension

Front:	Leaf springs with shock absorber
Rear:	Leaf springs

Cabin

Sleeper cab, Forward Control Type, Low Roof, New Face, All Welded Steel
 Cab of tilt type, Electromotional cab tilting, Rear Mechanical Cab Suspension
 Adjustable Driver's Seat, Air Conditioning System.

Type / Model	6x4 K24Y	8x4 K36Y
--------------	----------	----------

Tyres Battery

Front: Single	Voltage (V) : 24
Rear: Dual	Battery Capacity (A.h) 165x2
Size: 12.00R20	

Body Capacity

6x4 K24Y : 18cbm	8x4 K36Y : 26cbm
------------------	------------------



Note : The above mentioned parameters are only for your reference, please check real vehicle referring to actual equipment.

Dealer


DONGFENG
 Trucks